

# Victaulic® QuickVic™ Flexible Coupling

## Style 177N



2 – 8"/DN50 – DN200

### 1.0 PRODUCT DESCRIPTION

#### Available Sizes

- 2 – 8"/DN50 – DN200

#### Pipe Material

- Carbon steel; Stainless steel.
- For exceptions reference section 6.0 Notifications.

#### Maximum Working Pressure

- Accommodates pressures ranging from full vacuum (29.9 in Hg/760 mm Hg) up to 1000 psi/6900 kPa.
- Working pressure dependent on material, wall thickness and size of pipe.

#### Operating Temperature

- Dependent on gasket selection from section 3.0.

#### Function

- Joins roll or cut grooved pipe, grooved fittings, valves, and accessories.
- Provides a flexible pipe joint designed to accommodate a limited amount of linear and/or angular movement.

#### NOTE

- Applications that require NSF 61-approved products should specify the Victaulic Installation-Ready™ Flexible Coupling Style 877N ([publication 06.29](#)).

#### Pipe Preparation

- Cut or roll grooved in accordance with [publication 25.01](#): Victaulic Standard Groove Specifications.

### 2.0 CERTIFICATION/LISTINGS



EN 10311  
CPR (EU)  
No. 305/2011

BS EN 10311  
CPR (UK)  
2019 No. 465

#### NOTE

- See [publication 10.01](#): Victaulic Products for Fire Protection Piping Systems - Regulatory Approval Reference Guide for details.

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.

---

### 3.0 SPECIFICATIONS – MATERIAL

---

**Housing:** Ductile iron conforming to ASTM A536, Grade 65-45-12. Ductile iron conforming to ASTM A395, Grade 65-45-15 available upon special request.

**Housing Coating: (specify choice)**

Standard: Orange enamel.

Optional: Hot dipped galvanized conforming to ASTM A123.

Optional: Contact Victaulic with your requirements for other coatings.

**Gasket: (specify choice<sup>1</sup>)**

**Grade "EHP" EPDM**

EHP (Red and Green or Yellow and Green Stripes color code). Temperature range –30°F to +250°F/–34°C to +121°C. May be specified for hot water service within the specified temperature range plus a variety of dilute acids, oil-free air and many chemical services. NOT COMPATIBLE WITH PETROLEUM SERVICES.

**Grade "T" Nitrile**

Nitrile (Orange stripe color code). Temperature range –20°F to +180°F/–29°C to +82°C. May be specified for petroleum products, air with oil vapors, vegetable and mineral oils within the specified temperature range. Not compatible with hot water services over +150°F/+66°C or for hot dry air over +140°F/+60°C.

**Grade "HMT" Nitrile (North America only)**

Nitrile (Orange and Silver or Orange and Yellow Stripe color code). Temperature range –20°F to +180°F/–29°C to +82°C. May be specified for petroleum products, air with oil vapors, vegetable and mineral oils within the specified temperature range. Not compatible with hot water services over +150°F/+66°C or for hot dry air over +140°F/+60°C.

**Grade "O" Fluoroelastomer**

Fluoroelastomer (Blue stripe color code). Temperature range +20°F to +300°F/–7°C to +149°C. May be specified for many oxidizing acids, petroleum oils, halogenated hydrocarbons, lubricants, hydraulic fluids, organic liquids and air with hydrocarbons. NOT COMPATIBLE FOR USE WITH HOT WATER SERVICES OR STEAM SERVICES.

**Others**

For alternate gasket selection, reference [publication 05.01](#). Victaulic Seal Selection Guide - Elastomeric Seal Construction.

<sup>1</sup> Services listed are General Service Guidelines only. It should be noted that there are services for which these gaskets are not compatible. Reference should always be made to the latest [Victaulic Gasket Selection Guide](#) for specific gasket service guidelines and for a listing of services which are not compatible.

**NOTE**

- Victaulic reserves the right to substitute equivalent and/or higher grade elastomer products.

**Bolts/Nuts: (specify choice<sup>2</sup>)**

Standard: Carbon steel oval neck track bolts meeting the mechanical property requirements of ASTM A449 (imperial) and ISO 898-1 Class 9.8 (M10-M16) Class 8.8 (M20 and greater). Carbon steel hex nuts meeting the mechanical property requirements of ASTM A563 Grade B (imperial - heavy hex nuts) and ASTM A563M Class 9 (metric - hex nuts). Track bolts and hex nuts are zinc electroplated per ASTM B633 ZN/FE5, finish Type III (imperial) or Type II (metric).

Optional: Stainless steel oval neck track bolts meeting the mechanical property requirements of ASTM F593, Group 2 (316 Stainless Steel), condition CW. Stainless steel heavy nuts meeting the mechanical property requirements of ASTM F594, Group 2 (316 stainless steel), condition CW, with galling reducing coating.

<sup>2</sup> Optional bolts/nuts are available in imperial size only.


## 4.0 DIMENSIONS

### Style 177N QuickVic™ Flexible Coupling

#### Dimensions for Determining Piping System Installation Clearances

Data in the below table is provided for system layout and installation purposes to ensure that adequate clearances are included in the piping system installation relative to other piping components or the building structure for both roll grooved and cut grooved pipe.

This is particularly important when the system is free floating, or contains no thrust anchors, and the coupling joints are installed with the pipe ends butted against the gasket<sup>4</sup>. If installed in this condition, when the piping is pressurized the joints will open to their full nominal pipe end separation<sup>5</sup>. This movement is cumulative and will be most significant in long runs of piping where multiple flexible couplings are installed in the butted condition.



Size		Nominal Range of Pipe End Separation <sup>3</sup>		Qty.	Bolt/Nut Size inches mm	Dimensions					Weight Approximate (Each) lb kg
Nominal inches DN	Actual Outside Diameter inches mm	Pipe Ends Butted Against Gasket <sup>4</sup> inches mm	Full Nominal Separation <sup>5</sup> inches mm			Pre-Assembled (Installation-Ready™ Condition)		Joint Assembled			
						X inches mm	Y inches mm	X inches mm	Y inches mm	Z inches mm	
2 DN50	2.375 inches 60.3 mm	0.13 inches 3.3 mm	0.25 inches 6.4 mm	2	½ x 3 M12 x 76	4.38 111	6.25 159	3.75 95	6.38 162	2.13 54	3.3 1.5
2½ DN65	2.875 inches 73.0 mm	0.13 inches 3.3 mm	0.25 inches 6.4 mm	2	½ x 3 M12 x 76	4.88 124	6.88 175	4.38 111	6.88 175	2.13 54	3.8 1.7
3 DN80	3.000 inches 76.1 mm	0.13 inches 3.3 mm	0.25 inches 6.4 mm	2	½ x 3 M12 x 76	5.00 127	6.88 175	4.38 111	6.91 176	2.13 54	4.0 1.8
4 DN100	3.500 inches 88.9 mm	0.13 inches 3.3 mm	0.25 inches 6.4 mm	2	½ x 3 ¼ M12 x 83	5.63 143	7.38 187	5.00 127	7.50 191	2.13 54	4.3 2.0
	4.250 inches 108.0 mm	0.18 inches 4.6 mm	0.38 inches 9.7 mm	2	¾ x 4 M16 x 101	6.88 175	9.13 232	5.88 149	9.25 235	2.38 60	7.1 3.2
	4.500 inches 114.3 mm	0.18 inches 4.6 mm	0.38 inches 9.7 mm	2	¾ x 4 M16 x 101	7.13 181	9.38 238	6.38 162	9.50 241	2.38 60	7.4 3.4
	5.250 inches 133.0 mm	0.18 inches 4.6 mm	0.38 inches 9.7 mm	2	¾ x 5 M20 x 127	7.88 200	11.00 279	7.00 178	11.13 283	2.38 60	10.3 4.7
	5.500 inches 139.7 mm	0.18 inches 4.6 mm	0.38 inches 9.7 mm	2	¾ x 5 M20 x 127	8.25 210	11.00 279	7.38 187	11.25 286	2.25 57	9.8 4.4
	5.5625 inches 141.3 mm	0.18 inches 4.6 mm	0.38 inches 9.7 mm	2	¾ x 5 M20 x 127	8.03 204	11.03 280	7.31 186	11.32 288	2.245 57	10 4.5
	6.250 inches 159.0 mm	0.18 inches 4.6 mm	0.38 inches 9.7 mm	2	¾ x 5 M20 x 127	9.00 229	11.88 302	8.13 206	11.88 302	2.38 60	11.4 5.2
	6.500 inches 165.1 mm	0.18 inches 4.6 mm	0.38 inches 9.7 mm	2	¾ x 5 M20 x 127	9.38 238	12.13 308	8.50 216	12.13 308	2.25 57	12.7 5.8
6 DN150	6.625 inches 168.3 mm	0.18 inches 4.6 mm	0.38 inches 9.7 mm	2	¾ x 5 M20 x 127	9.38 238	12.38 314	8.63 219	12.25 311	2.38 60	12.8 5.8
8 DN200	8.625 inches 219.1 mm	0.18 inches 4.6 mm	0.38 inches 9.7 mm	2	7/8 x 5 ½ M22 x 139	11.00 279	15.13 384	10.00 254	15.13 384	2.63 60	20.7 9.4

<sup>3</sup> These columns provide the nominal range of pipe end separation that may exist at the time of installation.

<sup>4</sup> The nominal pipe end separation when the pipe ends are butted against the gasket as illustrated in Figure 1.

<sup>5</sup> The full nominal pipe end separation when the pipe ends are separated fully as illustrated in Figure 2.




Figure 1




Figure 2

## 4.1 DIMENSIONS

### Style 177N QuickVic™ Flexible Coupling

#### Design and Installation - Linear Movement and Angular Deflection

Data in the table below provides the linear movement and joint deflection capabilities of each coupling. These mechanical properties of the flexible coupling can be used in the design of the piping system to accommodate curves in the piping system, settlement of the building structure, seismic movement, or thermally induced expansion or contraction of the piping.

The linear movement<sup>7</sup> can be used to accommodate any axial movement of the piping caused by thermally induced expansion or contraction of the pipe. When used in this manner, thrust anchors must be installed at changes in direction, at the ends of straight runs, or to divide long runs of pipe into more manageable sections and reduce movement at branch connections. Reference should be made to Victaulic [publication 26.02](#) for detailed instructions regarding determining thrust anchor or guide locations.

The joint deflection<sup>8,9</sup> can also be used to accommodate the axial change in length of the piping caused by thermally induced expansion or contraction of the piping through the controlled deflection of offsets at existing changes in direction of the piping. Again, refer to Victaulic [publication 26.02](#) for detailed instructions.


Size		Linear Movement per Coupling <sup>6,9</sup>	Joint Deflection <sup>9</sup>	
Range inches DN	Actual Outside Diameter inches mm		Angle at Coupling <sup>7</sup> Degrees per coupling	Slope of Pipe <sup>8</sup> in/ft mm/m
2	2.375	0.09	2.17	0.46
DN50	60.3	2.3		38.1
2½	2.875	0.09	1.79	0.38
	73.0	2.3		31.5
DN65	3.000	0.09	1.72	0.36
	76.1	2.3		30.2
3	3.500	0.09	1.47	0.31
DN80	88.9	2.3		25.9
	4.250	0.18	2.43	0.51
	108.0	4.6		42.6
4	4.500	0.18	2.29	0.48
DN100	114.3	4.6		40.3
	5.250	0.18	1.96	0.41
	133.0	4.6		34.6
	5.500	0.18	1.88	0.39
	139.7	4.6		32.9
5	5.5625	0.18	1.85	0.39
	141.3	4.6		32.4
	6.250	0.18	1.65	0.35
	159.0	4.6		28.9
	6.500	0.18	1.59	0.33
	165.1	4.6		27.9
6	6.625	0.18	1.56	0.33
DN150	168.3	4.6		27.3
8	8.625	0.18	1.20	0.25
DN200	219.1	4.6		21.0

<sup>6</sup> This is the actual net linear movement available at each coupling for design purposes as illustrated in Figures 1 and 2.


<sup>7</sup> This is the actual net deflection angle available at each coupling listed in degrees as illustrated in Figure 3.

<sup>8</sup> This is the actual net deflection angle available at each coupling listed as a slope of the pipe as illustrated in Figure 4.

<sup>9</sup> These values are the net amount of linear movement or joint deflection available at the couplings. No further reduction, as detailed in Victaulic [publication 26.02](#), is needed to allow for design and installation purposes.



Deflection Angle at Each Coupling Listed in Degrees  
Figure 3



Deflection Angle at Each Coupling Listed as a Slope of the Pipe  
Figure 4

**NOTE**

- A coupling joint cannot provide the full linear movement and full angular deflection at the same time. If both linear movement and angular deflection are needed, sufficient couplings must be installed for each purpose. Refer to Victaulic [publication 26.02](#) for complete details.

## 5.0 PERFORMANCE

### Style 177N QuickVic™ Flexible Coupling

#### ANSI/ISO Standards

Size		Schedule 10 and Thin Wall ISO (Steel Pipe)				Schedule 40 and ISO (Steel Pipe)			
Nominal	Actual Outside Diameter	ANSI Wall Thickness	ISO Wall Thickness	Max. <sup>10</sup> Joint Work Pressure	Max. <sup>10</sup> Permis. End Load	ANSI Wall Thickness	ISO Wall Thickness	Max. <sup>10</sup> Joint Work Pressure	Max. <sup>10</sup> Permis. End Load
inches DN	inches mm	inches mm	inches mm	psi kPa	lbs N	inches mm	inches mm	psi kPa	lbs N
2 DN50	2.375	0.109	0.091	750	3322	0.154	0.157	1000	4430
	60.3	2.77	2.3	5170	14780	3.91	4.0	6900	19706
2½	2.875	0.120	–	600	3895	0.230	–	1000	6492
	73.0	3.05	–	4135	17326	5.84	–	6900	28877
DN65	3.000	–	0.150	600	4240	–	0.200	1000	7070
	76.1	–	3.8	4135	18870	–	5.1	6900	31460
3 DN80	3.500	0.120	0.114	600	5773	0.216	0.197	1000	9621
	88.9	3.05	2.9	4135	25678	5.49	5.0	6900	42797
	4.250	–	0.114	600	8512	–	0.220	1000	14186
	108.0	–	2.9	4135	37861	–	5.6	6900	63102
4 DN100	4.500	0.120	0.126	600	9543	0.237	0.220	1000	15904
	114.3	3.05	3.2	4135	42448	6.02	5.6	6900	70746
	5.250	–	0.126	600	12989	–	0.248	1000	21648
	133.0	–	3.2	4135	57774	–	6.3	6900	96290
	5.500	–	0.150	500	11879	–	0.220	1000	23758
	139.7	–	3.8	3445	52840	–	5.1	6900	105680
5	5.563	0.134	–	500	12151	0.258	–	1000	24301
	141.3	3.4	–	3448	54046	6.55	–	6897	108092
	6.250	–	0.126	600	18408	–	0.280	1000	30680
	159.0	–	3.2	4135	81879	–	7.1	6900	136465
	6.500	–	0.177	450	14932	–	0.280	1000	33183
	165.1	–	4.5	3100	66243	–	7.1	6900	147605
6 DN150	6.625	0.134	0.157	450	15512	0.280	0.280	1000	34470
	168.3	3.40	4.0	3100	69000	7.11	7.1	6900	153390
8 DN200	8.625	0.148	0.177	300	17525	0.322	0.315	800	46732
	219.1	3.76	4.5	2065	77950	8.18	8.0	5500	207836

<sup>10</sup> Working Pressure and End Load are total, from all internal and external loads, based on (ANSI) steel pipe, grooved in accordance with Victaulic specifications. Contact Victaulic for performance on other pipe.

#### NOTES

- WARNING: FOR ONE TIME FIELD TEST ONLY, the Maximum Joint Working Pressure may be increased to 1½ times the figures shown.
- Depressurize and drain the piping system before attempting to install, remove or adjust any Victaulic piping products.
- FM approved on Schedule 10 pipe: 2 – 6 inch sizes rated to 365 psi/25 bar; and 8 inch size (.188" wall thickness) rated to 365 psi/25 bar. Schedule 40 pipe: 2 – 8 inch sizes rated to 365 psi/25bar.
- UL listed on Schedule 10 pipe: 2-6 inch sizes rated to 365 psi/25bar; and 8 inch size (.188" wall thickness) rated to 365 psi/25 bar. Schedule 40 pipe: 2 – 3 inch sizes rated to 840 psi/58 bar; and 4-6 inch sizes rated to 600 psi/41 bar; and 8 inch size rated to 500 psi/34 bar.

## 6.0 NOTIFICATIONS

### WARNING



- Read and understand all instructions before attempting to install, remove, adjust, or maintain any Victaulic piping products.
- Depressurize and drain the piping system before attempting to install, remove, adjust, or maintain any Victaulic piping products.
- Always confirm that any equipment, branch lines, or sections of piping that may have been isolated for/during testing or due to valve closures/positioning are identified, depressurized, and drained immediately prior to working with an end cap.
- Wear safety glasses, hardhat, and foot protection.

Failure to follow these instructions could result in death or serious personal injury and property damage.

### WARNING

- Victaulic RX roll sets must be used when grooving light-wall/thin-wall stainless steel pipe for use with Victaulic Couplings.
- Victaulic RX grooving rolls must be ordered separately. They are identified by a silver color and the designation RX on the front of the roll sets.

Failure to use Victaulic RX roll sets when grooving light-wall/thin-wall stainless steel pipe may cause joint failure, resulting in serious personal injury and/or property damage.

### WARNING

- When assembling Style 107V Couplings onto end caps, take additional time to inspect and verify that the end cap is seated fully against the center leg of the gasket. Always read and follow the installation instructions provided with the product; these instructions can be downloaded at [Victaulic.com](http://Victaulic.com).
- Use only Victaulic End Caps containing the “QV” or “EZ QV” marking on the inside face.
- Always read and follow the I-ENDCAP, Victaulic End Cap Installation Safety Instructions, which can be downloaded at [Victaulic.com](http://Victaulic.com).
- Victaulic recommends the use of Victaulic fittings with Style 177N Couplings.

Failure to follow these instructions could result in death or serious personal injury and property damage.

### NOTICE

- Victaulic does not recommend the use of any furnace butt-welded pipe with sizes NPS 2”/DN50 and smaller Victaulic gasketed joint products. This includes, but is not limited to, ASTM A53 Type F pipe.

## 7.0 REFERENCE MATERIALS

[05.01: Victaulic Seal Selection Guide](#)

[06.29: Victaulic QuickVic™ Installation-Ready™ Flexible Coupling for Potable Water Applications Style 877N](#)

[10.01: Victaulic Fire Protection Certifications/Listings Reference Guide](#)

[17.01: Victaulic Pipe Preparation for Use on Stainless Steel Pipe With Victaulic Products](#)

[17.09: Victaulic Pressure Ratings and End Loads for Victaulic Ductile Iron Grooved Couplings on Stainless Steel Pipe](#)

[26.01: Victaulic Design Data](#)

[29.01: Victaulic Terms and Conditions/Warranty](#)

[I-100: Victaulic Field Installation Handbook](#)

[I-177N: Victaulic QuickVic™ Installation-Ready™ Flexible Coupling Installation Instructions](#)

[I-ENDCAP: Victaulic End Caps Installation Instructions](#)

[I-IMPACT: Victaulic Impact Tool Usage Guidelines](#)

### User Responsibility for Product Selection and Suitability

Each user bears final responsibility for making a determination as to the suitability of Victaulic products for a particular end-use application, in accordance with industry standards and project specifications, and the applicable building codes and related regulations as well as Victaulic performance, maintenance, safety, and warning instructions. Nothing in this or any other document, nor any verbal recommendation, advice, or opinion from any Victaulic employee, shall be deemed to alter, vary, supersede, or waive any provision of Victaulic Company's standard conditions of sale, installation guide, or this disclaimer.

### Intellectual Property Rights

No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Victaulic or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right. The terms "Patented" or "Patent Pending" refer to design or utility patents or patent applications for articles and/or methods of use in the United States and/or other countries.

### Note

This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

### Installation

Reference should always be made to the [Victaulic installation handbook](#) or installation instructions of the product you are installing. Handbooks are included with each shipment of Victaulic products, providing complete installation and assembly data, and are available in PDF format on our website at [www.victaulic.com](http://www.victaulic.com).

### Warranty

Refer to the Warranty section of the current Price List or contact Victaulic for details.

### Trademarks

*Victaulic* and all other Victaulic marks are the trademarks or registered trademarks of Victaulic Company, and/or its affiliated entities, in the U.S. and/or other countries.