System Data

Viega MegaPress[®] 316 Fittings



MegaPress 316 fittings are designed to be used with standard IPS ASTM A312 stainless steel pipe and are ideal for industrial applications. MegaPress 316 1/2" to 2" fittings can be used with Schedule 5 to Schedule 40 stainless steel pipe and 21/2" to 4" fittings can be used with Schedule 10 to Schedule 40

stainless steel pipe. A MegaPress 316 system can stand up to harsh environments while transporting process water, potable water, ammonia, low pressure steam or any number of other essential fluids or gases. MegaPress 316 fittings in sizes from 1/2" to 4" are offered in configurations including: elbows, couplings, reducers, tees, reducing tees, threaded adapters, unions, caps and flanges.

Components

- Alloy: 316 stainless steel
- EPDM sealing element
- 420 stainless steel grip ring .
- 304 stainless steel separator ring for 1/2" to 2" fittings
- PBT separator ring for 21/2" to 4" fittings

Operating Parameters

Operating Pressure:	200 psi max
Operating Temperatures:	0° to 250 °F

Operating Temperatures:

Listings and Certificates

- ABS type approval
- Lloyd's Register
- ASME B31.1, B31.3, B31.9 NFPA 13, 13D, 13R BV (Bureau Veritas) .
 - NSF/ANSI 61
- CRN 23076.5 A/B/C
- DNV-GL

- - 3" only)

Compliant With

IAPMO PS117

ICC-ES LC1002

- IAPMO California Plumbing Code (CPC)
- IAMPO National Standard Plumbing Code (NSPB)
- IAPMO Uniform Mechanical Code (UMC)
- ASME B31 ASTM A312 ASTM A554
- IAPMO Uniform Plumbing Code (UPC)
- ICC International Mechanical Code (IMC)
- ICC International Plumbing Code (IPC)
- ICC International Residential Code (IRC)
- National Building Code of Canada (NBCC)
- National Plumbing Code of Canada (NPCC)

Viega LLC

585 Interlocken Blvd. Broomfield, CO 80021

Phone (800) 976-9819 www.viega.us

SD-MP 0321 MegaPress 316

Approved Applications

- Low pressure steam
- Industrial gases
- Potable water
- Caustic solutions
- Acid solutions
- Vacuum
- Process water (non-potable)

For more specific information on applications for MegaPress 316, contact Viega Technical Services at 1-800-976-9819.

MegaPress 316 systems are approved for underground use. When installed underground, MegaPress 316 should have proper corrosion protection in accordance with local and national codes.

Recommended Tools

- Standard size press tool (minimum hydraulic ram output of 7200 lbs.)
- #56013 MegaPress jaw/ring kit (1/2" to 2")
- #26200 MegaPress XL PressBooster with 21/2" press ring
- #26201 MegaPress XL 3" and 4" press ring kit
- #57081 Z3 Actuator with 2½" ring (must be used with press gun with minimum 80mm press stroke)

Smart Connect[®] Technology

MegaPress 316 fittings are manufactured with Viega's unique Smart Connect technology. A design of the fitting, Smart Connect technology allows identifications of an unpressed fitting during pressure testing.



This document is subject to updates. For the most current Viega technical literature please visit www.viega.us.



Viega products are designed to be installed by licensed and trained plumbing and mechanical professionals who are familiar with Viega products and their installation. Installation by

non-professionals may void Viega LLC's warranty.



NSF/ANSI 372 FM Class 1920 (½" to 2" only) ANSI/CAN/UL 213 (1/2" to