

XXX SPECIALTY ADHESIVE REMOVER

IMPORTANT NOTE:

For batch codes dated May 2020 and after, refer to SDS found on pages 2 – 13.

For all other batch code numbers refer to pages 14 – 24.

Batch code numbers are found on the bottom of the can, printed below the part number. To read batch code date, refer to the first 3 digits. First digit identifies the year. Second and third digits identify the month.

Ex: Batch Code 005140 was made in May (05) of 2020 (0).

For questions contact technical support at 800-831-1122.

SEM

Printing date 01/08/2020 Version number 15 Reviewed on 01/08/2020

1 Identification

- · Product identifier
- · Trade name: XXX Specialty Adhesive Remover
- · Article number: 77783
- · Application of the substance / the mixture Exterior vehicle cleaner
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803-207-8225

· Information department:

cust_care@semproducts.com,1685 OverviewDr. Rock Hill SC 29730:phone 1-800-831-1122, M-Th 7am-4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

 (Contd. on page 2)

HSA.

Version number 15 Printing date 01/08/2020 Reviewed on 01/08/2020

Trade name: XXX Specialty Adhesive Remover

(Contd. of page 1)

· Hazard pictograms









GHS04

· Signal word Danger

· Hazard-determining components of labeling:

Solvent naphtha (petroleum), light aliph.

acetone

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

regulations.

Precautionary statements

1 recultionary state	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international

(Contd. on page 3)

Reviewed on 01/08/2020

Version number 15 Printing date 01/08/2020

Trade name: XXX Specialty Adhesive Remover

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 4Reactivity = 3

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous	components:	
67-64-1	acetone	30-40%
1330-20-7	xylene	13-30%
64742-89-8	Solvent naphtha (petroleum), light aliph.	13-30%
68476-86-8	Petroleum gases, liquefied, sweetened	7-10%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)

SEM

Printing date 01/08/2020 Version number 15 Reviewed on 01/08/2020

Trade name: XXX Specialty Adhesive Remover

(Contd. of page 3)

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
67-64-1	acetone	200 ppm
1330-20-7	xylene	130 ppm
· PAC-2:		
67-64-1	acetone	3200* ppm
1330-20-7	xylene	920* ppm
· PAC-3:		
	acetone	5700* ppm
1330-20-7	xylene	2500* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 5)

Version number 15 Printing date 01/08/2020 Reviewed on 01/08/2020

Trade name: XXX Specialty Adhesive Remover

(Contd. of page 4)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

67-64-1 acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m³, 250 ppm TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI

Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine *Time: end of shift*

Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine *Time: end of shift*

Parameter: Methylhippuric acids

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

et SE

Printing date 01/08/2020 Version number 15

Reviewed on 01/08/2020

Trade name: XXX Specialty Adhesive Remover

(Contd. of page 5)

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

. / 10 1	AUM ATIAN	AN BACK	a mhuician	I and a	hominal	nuanautiac
1111	<i>() </i>	vii vusii	. muvsicu	ı unu c	петиси	properties

· General Information

· Appearance:

· pH-value:

Form: Aerosol

Color: According to product specification

Odor: CharacteristicOdor threshold: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:55.8-56.6 °C

· Flash point: -103 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 500 °C

· **Decomposition temperature:** Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Not determined.

· Explosion limits:

 Lower:
 1.1 Vol %

 Upper:
 9.5 Vol %

(Contd. on page 7)

SEM

Printing date 01/08/2020 Version number 15 Reviewed on 01/08/2020

Trade name: XXX Specialty Adhesive Remover

	(Contd. c	of page
Vapor pressure at 20 °C:	14 hPa	
Density at 20 °C:	0.76103 g/cm^3	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/v	water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	100.0 %	
VOC content:	68.00 %	
	748.1 g/l / 6.24 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC5	0 valu	es that are relevant for classification:
1330-20	. •	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

The product can cause inheritable damage.

(Contd. on page 8)

SEM

Printing date 01/08/2020 Version number 15 Reviewed on 01/08/2020

Trade name: XXX Specialty Adhesive Remover

(Contd. of page 7)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes: Not hazardous for water.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

411	7 7			C	
14	Iran	snori	TIN	formai	สภท

- · UN-Number
- · **DOT, ADR, IMDG, IATA** UN1950
- · UN proper shipping name

DOT Aerosols, flammable
 ADR 1950 AEROSOLS
 IMDG AEROSOLS

· IATA AEROSOLS, flammable

(Contd. on page 9)

USA

Version number 15 Reviewed on 01/08/2020 Printing date 01/08/2020

Trade name: XXX Specialty Adhesive Remover

(Contd. of page 8) · Transport hazard class(es) $\cdot DOT$ · Class 2.1 ·Label 2.1 $\cdot ADR$ · Class 2 5F Gases · Label 2.1 · IMDG, IATA 2.1 · Class ·Label 2.1 · Packing group · DOT, ADR, IMDG, IATA Void · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Gases F-D,S- \bar{U} · EMS Number: · Stowage Code SW1 Protected from sources of heat. SW2 Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code *Not applicable.* · Transport/Additional information: $\cdot DOT$ On passenger aircraft/rail: 75 kg Quantity limitations On cargo aircraft only: 150 kg (Contd. on page 10)

SEM

Printing date 01/08/2020 Version number 15

Reviewed on 01/08/2020

Trade name: XXX Specialty Adhesive Remover

· ADR
· Excepted quantities (EQ)

· IMDG
· Limited quantities (LQ)
· Excepted quantities (LQ)
· Excepted quantities (EQ)

· Low the permitted as Excepted Quantity

IL
· Excepted quantities (EQ)

Code: E0
Not permitted as Excepted Quantity

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

Sara Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	
Section 313 (Specific toxic chemical listings):	
1330-20-7 xylene	
TSCA (Toxic Substances Control Act):	
67-64-1 acetone	ACT
1330-20-7 xylene	ACT
68476-86-8 Petroleum gases, liquefied, sweetened	ACT
Hazardous Air Pollutants	
1330-20-7 xylene	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
1330-20-7 xylene	
Cancerogenity categories	
EPA (Environmental Protection Agency)	
67-64-1 acetone	
1330-20-7 xylene	
TLV (Threshold Limit Value established by ACGIH)	
67-64-1 acetone	
1330-20-7 xylene	



Version number 15 Reviewed on 01/08/2020 Printing date 01/08/2020

Trade name: XXX Specialty Adhesive Remover

(Contd. of page 10)

· Hazard pictograms









· Signal word Danger

· Hazard-determining components of labeling:

Solvent naphtha (petroleum), light aliph.

acetone

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Precautionary state	ements
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
DAGG DAIA	

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. P332+P313 If eye irritation persists: Get medical advice/attention. P337+P313 P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

(Contd. on page 12)

SEM

Printing date 01/08/2020 Version number 15 Reviewed on 01/08/2020

Trade name: XXX Specialty Adhesive Remover

(Contd. of page 11)

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Andy French (AFrench@semproducts.com)
- · Date of preparation / last revision 01/08/2020 / 14
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure - Compressed gas

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

· * Data compared to the previous version altered.

USA

IMPORTANT NOTE:

The following pages contain the SDS for batch code numbers prior to May 2020.

Batch code numbers are found on the bottom of the can, printed below the part number. To read batch code date, refer to the first 3 digits. First digit identifies the year. Second and third digits identify the month.

Ex: Batch Code 005140 was made in May (05) of 2020 (0).

For questions contact technical support at 800-831-1122.



Printing date 03/14/2018 Reviewed on 06/28/2017

1 Identification

· Product identifier

· Trade name: 77783 Universal Adhesive Remover

· Article number: 77783

- · Application of the substance / the mixture Cleaner solvent / adhesive remover
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730

803 207 8225

· Information department:

cust_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture





GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

2 GHS04

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling: Solvent naphtha (petroleum), light aliph.
- · Hazard statements

H222 Extremely flammable aerosol.

(Contd. on page 2)

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 77783 Universal Adhesive Remover

(Contd. of page 1)

H280 Contains gas under pressure; may explode if heated.

H340 May cause genetic defects.

H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. P251

Wear protective gloves/protective clothing/eye protection/face protection. P280

P301+P310 If swallowed: Immediately call a poison center/doctor.

P331 Do NOT induce vomiting.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 4Reactivity = 3

· HMIS-ratings (scale 0 - 4)



Health = *0Fire = 4

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

Mixture: consisting of the following components.

Weight percentages

· Dangerous components:	
64742-89-8 Solvent naphtha (petroleum), light aliph.	70-100%
68476-86-8 Petroleum gases, liquefied, sweetened	13-30%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 77783 Universal Adhesive Remover

(Contd. of page 2)

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: No special measures required.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

None of the ingredients is listed.

· PAC-2:

None of the ingredients is listed.

· PAC-3:

None of the ingredients is listed.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

 $\cdot \textit{Information about protection against explosions and fires:} \\$

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 77783 Universal Adhesive Remover

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses

(Contd. on page 5)


USA

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 77783 Universal Adhesive Remover

(Contd. of page 4)



Information on basic physical and	chemical properties
General Information	r. · · · · · · · · · · · · · · · · · · ·
Appearance:	
Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	36 °C
Flash point:	-103 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	265 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.9 Vol %
Upper:	9.5 Vol %
Vapor pressure at 20 °C:	14 hPa
Density at 20 °C:	$0.68909 \ g/cm^3$
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	t er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.00 %
	689.1 g/l / 5.75 lb/gl

(Contd. on page 6)

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 77783 Universal Adhesive Remover

(Contd. of page 5)

Solids content: 0.0 %

• *Other information No further relevant information available.*

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: The product can cause inheritable damage.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 77783 Universal Adhesive Remover

· Other adverse effects No further relevant information available.

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN1950
UN proper shipping name DOT	Aerosols, flammable
ADR IMDG IATA	1950 Aerosols AEROSOLS AEROSOLS, flammable
Transport hazard class(es)	TEROSOES, Januaraote
DOT	
Luciana III	
Class	2.1
Label	2.1
ADR	
Class	2 5F Gases
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
Packing group DOT, ADR, IMDG, IATA	Void

(Contd. on page 8)

SEM

Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 77783 Universal Adhesive Remover

	(Contd. of page 7
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Warning: Gases
· EMS Number:	F- D , S - U
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class 1 except fo division 1.4. For AEROSOLS with a capacity above 1 litre Segregation as for the appropriate subdivision of class 2. Fo WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	
· DOT	
Quantity limitations	On passenger aircraft/rail: 75 kg
	On cargo aircraft only: 150 kg
· ADR	
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities $(\widetilde{E}Q)$	Code: E0
	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

64742-89-8 Solvent naphtha (petroleum), light aliph.

· TSCA new (21st Century Act) (Substances not listed)

68476-86-8 Petroleum gases, liquefied, sweetened

(Contd. on page 9)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 77783 Universal Adhesive Remover

(Contd. of page 8)

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GHS04 G

- · Signal word Danger
- · Hazard-determining components of labeling:

Solvent naphtha (petroleum), light aliph.

· Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H340 May cause genetic defects.

H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P331 Do NOT induce vomiting.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 10)



Printing date 03/14/2018 Reviewed on 06/28/2017

Trade name: 77783 Universal Adhesive Remover

(Contd. of page 9)

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- · Date of preparation / last revision 03/14/2018 / 8
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Aerosol 1: Aerosols - Category 1

Press. Gas: Gases under pressure - Compressed gas

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1B: Carcinogenicity - Category 1B

Asp. Tox. 1: Aspiration hazard - Category 1

* * Data compared to the previous version altered.

USA