

# IPEX INDUSTRIAL PRODUCT OVERVIEW

## Xirtec® PVC – Xirtec® CPVC

1/2" – 24" (12mm – 600mm)

XIRTEC®: PVC Schedule 40  
& 80 pipe and fittings systems.

XIRTEC®: CPVC Schedule 80  
pipe and fittings systems  
cell classification 24448 & 23447



## Duraplus™

## ABS Industrial

1/2" – 12" (12mm – 300mm)

Complete ABS pressure  
pipe, valves and fitting systems.



## PROCESS PIPING SYSTEMS



## Enpure™

1/2" – 4" (12mm – 100mm)

High-purity polypropylene pipe, valves, and  
fittings with a socket fusion joining system.



## CORROSIVE WASTE SYSTEMS



## Enfield™

1-1/2" – 12" (40mm – 300mm)

Electrofusion corrosive waste  
system consists of Polypropylene  
Schedule 40 & 80 IPS pipe  
and fittings.



## Labline®

1-1/2" – 4" (40mm – 100mm)

Mechanical joint corrosive  
waste system in polypropylene  
Schedule 40 and 80 IPS pipe  
(flame-retardant and non-  
flame-retardant) and fittings.



## Plenumline™

1-1/2 – 4" (40mm – 100mm)

Flame-retardant PVDF mechanical joint  
acid waste system made for return air  
plenum high-temperature corrosive  
chemical waste applications.



## THERMOPLASTIC VALVES

### Thermoplastic Valves

1/2" – 16" (12mm – 400mm)

IPEX offers a variety of manual & actuated  
valves in PVC, CPVC, PP, PVDF and ABS.



## Guardian™

Carrier: 1/2" – 12" (12mm – 300mm)  
Containment: 2" – 18" (50mm – 450mm)

Vinyl double containment and leak detection system in tough industrial grade PVC and high temperature CPVC.



# DOUBLE CONTAINMENT SYSTEMS



## CustomGuard™

Carrier: 1/2" – 20" (12mm – 500mm)  
Containment: 2" – 26" (50mm – 660mm)

Custom designed and fabricated double containment systems for similar & dissimilar materials.



## Duratec® Airline

1/2" – 1" (12mm – 25mm)

Composite pipe and fittings for conveying compressed air and inert gases.



# SPECIALTY PRODUCTS

## Ventilation Duct

PVC 6" – 24" (150mm – 600mm)  
CPVC 6" – 16" (150mm – 400mm)

Seamless PVC & CPVC ventilation duct systems for corrosive fume handling applications.



## Well Casings

2" – 16" (50mm – 400mm)

PVC corrosion-resistant, maintenance-free casings for well-drop-pipe and submersible pumps.



## Grooved PVC Pipe

2" – 24" (50mm – 600mm)

Schedule 40, 80, SDR 26 and SDR 21 factory-grooved PVC pipe.

