

Pump Accessories

Sanitary Well Seals

Two-piece, cast iron construction. Rubber Composition Seal.

459S - One Pipe

- 4" well..... 1", 1 1/4"
- 4 1/2" well .. 1 1/4"
- 5" well..... 1", 1 1/4"
- 5 5/8" well .. 1", 1 1/4"
- 6" well..... 1", 1 1/4", 1 1/2", 2"



460S - Two Pipe

- 4" well..... 1 1/4" x 1"
- 5" well..... 1 1/4" x 1"
- 5 5/8" well .. 1 1/4" x 1"
- 6" well..... 1 1/4" x 1"
- 6" well..... 1 1/2" x 1 1/4"



Plastic Sanitary Well Seals

Two-piece, plastic construction. Rubber Composition Seal.



- 401S - 4" well.....1"
- 402S - 4" well.....1 1/4"
- 451S - 4 1/2" well..... 1"
- 452S - 4 1/2" well 1 1/4"
- 453S - 4 1/2" well 1 1/2"
- 501S - 5" well..... 1"
- 601S - 6" well..... 1"
- 602S - 6" well..... 1 1/4"

Also available in two pipe, contact factory.

Air Volume Controls

Float Types

894 3129-383 Deep Well



Diaphragm type

- 30-AV 3129-378 - 1/4"
- 42-AV 3129-388 - 1/4"
- 80-AV 3129-379 - 1/4"
- 120-AV 3129-380 - 3/8"
- 45-AV 3129-389 - 1/4"
- 100-AV 3129-386 - 3/8"



REPAIR KITS available (see price list)

Float & Valve

8713 Float Valve

18" long - 3/4" or 1"
Repair Parts available (see price list)



8715 Floats for Float Valve

3" x 12" diameter float



Pressure Gauge

5999-897 Pressure Gauge

0-100 lbs. - 2" Dial - MPT. 1/4" Brass stem.
Steel case, Vertical installation



For electrical accessories, please see price list.

"FSG" Pressure switches are rated to 1 1/2 HP, 115V, single phase and/or 2 HP, 230V, single phase or up to 3 HP, 230V, three phase. Submersible pumps above 2 HP, one phase require deluxe control boxes with these switches.

Switches

A.Y. McDonald

Model No.	Size	Setting	Model
3129-421	1/4"	20-40	(9013FSG2J20)
3129-423	1/4"	30-50	(9013FSG2J21)
3129-432	1/4"	40-60	(9013FSG2J24)
3129-442	1/4"	20-40	(9013FSG2J20C20) 20 pack
3129-443	1/4"	30-50	(9013FSG2J21C20) 20 pack
3129-448	1/4"	40-60	(9013FSG2J24C20) 20 pack



Switches with "P" include pulsation plug to dampen surges to the switch

3129-414	1/4"	20-40	(9013FSG2J20P)
3129-436	1/4"	30-50	(9013FSG2J21P)

A.Y. McDonald

Model No.	Size	Setting	Model
Switches with "M4" include auto cut-off if pressure drops to about 10 PSIG below cut-in pressure - requires manual reset with lever provided.			
3129-420	1/4"	20-40	(9013FSG2J20M4)
3129-433	1/4"	30-50	(9013FSG2J21M4)
3129-438	1/4"	40-60	(9013FSG2J24M4)



Switches with "M1" include manual cut-off lever to allow circuit interruption at the switch to service the pump.

3129-439	1/4"	30-50	(9013FSG2J21M1)
----------	------	-------	-----------------

A.Y. McDonald

Model No.	Size	Setting	Model
"GSG" heavier duty switches are rated to 3 HP 230 V. Single phase and 5 HP 230 V. Three phase plus DC to 1 HP. They require use of deluxe control boxes on submersible pumps above 3 HP single phase.			
3129-430	1/4"	20-40	(9013GSG2J20)
3129-435	1/4"	30-50	(9013GSG2J21)
3129-434	1/4"	40-60	(9013GSG2J24)



A.Y. McDonald

Model No.	Size	Setting
3129-457	1/4"	20-40
3129-458	1/4"	30-50
3129-459	1/4"	40-60

