

Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

PLASTIC TEST CAPS

- Seal pipe ends economically
- For use on schedule 40 ABS and PVC DWV pipe

238 701	1-1/2"	Knock-Out™ Test Cap	100/1500	13 PSI	30FT
238 702	2"	Knock-Out™ Test Cap	100/1200	13 PSI	30FT
238 703	3"	Knock-Out™ Test Cap	50/500	13 PSI	30FT
238 704	4"	Knock-Out™ Test Cap	25/300	13 PSI	30FT
228 108	1-1/2"	Push-Cap™ Test Cap	50/250	4.3 PSI	10FT
228 208	2"	Push-Cap™ Test Cap	25/150	4.3 PSI	10FT
228 308	3"	Push-Cap™ Test Cap	10/100	4.3 PSI	10FT
228 408	4"	Push-Cap™ Test Cap	10/50	4.3 PSI	10FT
238 108	1-1/2"	End-Cap™ Test Cap	100/1000	17 PSI	40FT
238 208	2"	End-Cap™ Test Cap	100/800	17 PSI	40FT
238 308	3"	End-Cap™ Test Cap	50/400	17 PSI	40FT
238 408	4"	End-Cap™ Test Cap	20/200	17 PSI	40FT
238 128	1-1/2"-2"	MS End-Cap™ Test Cap	50/500	17 PSI	40FT
238 348	3"- 4"	MS End-Cap™ Test Cap	25/200	17 PSI	40FT



PVC TEST-KAP® PLUGS

- Stainless steel hose clamp won't corrode
- Reinforced cross-molded top increases strength
- For use on plastic, steel, copper, and cast-iron pipe
- Tighten clamp with torque wrench or screwdriver to 60 inch pounds

270 725	1-1/2"	Test-Kap® Plug	10	13 PSI	30FT
270 733	2"	Test-Kap® Plug	10	13 PSI	30FT
270 741	3"	Test-Kap® Plug	10	13 PSI	30FT
270 768	4"	Test-Kap® Plug	10	13 PSI	30FT
270 776	5"	Test-Kap® Plug	5	13 PSI	30FT
270 784	6"	Test-Kap® Plug	5	13 PSI	30FT



TUB WASTE & OVERFLOW PLUGS

- Used to isolate bath wastes for air/water testing
- Yellow ABS plastic ensures easy job site recognition
- Natural rubber gasket creates air-tight seal
- For use on center hole drains overflow
- 3/8" Drain thread
- 1/4" Overflow thread

012 678	Tub Plug Set (overflow & drain)	12
---------	---------------------------------	----

MANOMETER

- Used for final test of DWV pipe and to test gas lines
- Measures water columns from 0" to 16"
- Reads in 1/10" increments

010 205	Manometer	1
---------	-----------	---



CLOG-BUSTER® DRAIN FLUSHER

- Unclogs drain pipes in seconds
- Attaches to standard garden hose fitting
- Simply remove aerator from faucet spigot and attach faucet adapter to garden hose
- Natural rubber body provides excellent seal

303 127	1"-2"	Drain Flusher	1
303 135	1-1/2"-3"	Drain Flusher	1
303 143	4"- 6"	Drain Flusher	1
006 193	Faucet Adapter	1	



Cherne manufactures plugs to 96" in diameter, hydrostatic test pumps, along with a complete line of sewer testing equipment. Go to www.cherneind.com for our complete offering or contact customer service for a full line catalog