

Safety Switches General Duty, Type TG

Spec-Setter™ Safety Switches

30-600 Amperes

240 Volts AC

250 Volts DC

Section 4

Fusible, Two-pole, 120/240 and 240 Volts AC; 250 Volts DC (30-100 amps only); Three-wire SN, 240 Volts AC

Ampere Rating	Enclosure Type	HP, 240 Vac, NEC Std, 1-ph	HP, 240 Vac, NEC Std, 3-ph	HP, 240 Vac, Time Delay, 1-ph	HP, 240 Vac, Time Delay, 3-ph	HP, 125 Vdc	HP, 250 Vdc	Product Number
30A	NEMA Type 1	1 1/2	3	3	7 1/2	2	5	TG3221 ¹
60A	NEMA Type 1	3	7 1/2	10	15	3	10	TG3222
100A	NEMA Type 1	7 1/2	15	15	30	–	20	TG3223
200A	NEMA Type 1	15	25	15	50	–	–	TG3224
400A	NEMA Type 1	–	50	–	100	–	–	TG3225
600A	NEMA Type 1	–	75	–	100	–	–	TG3226
30A	NEMA Type 3R	1 1/2	3	3	7 1/2	2	5	TG3221R
60A	NEMA Type 3R	3	7 1/2	10	15	3	10	TG3222R
100A	NEMA Type 3R	7 1/2	15	15	30	–	20	TG3223R
200A	NEMA Type 3R	15	25	15	50	–	–	TG3224R
400A	NEMA Type 3R	–	50	–	100	–	–	TG3225R
600A	NEMA Type 3R	–	75	–	100	–	–	TG3226R

Fusible, Three-pole, 240 Volts AC; 250 Volts DC (30-100 amps only)

Ampere Rating	Enclosure Type	HP, 240 Vac, NEC Std, 1-ph	HP, 240 Vac, NEC Std, 3-ph	HP, 240 Vac, Time Delay, 1-ph	HP, 240 Vac, Time Delay, 3-ph	HP, 125 Vdc	HP, 250 Vdc	Product Number
30A	NEMA Type 1	1 1/2	3	3	7 1/2	–	5	TG4321 ¹
60A	NEMA Type 1	3	7 1/2	10	15	3	10	TG4322
100A	NEMA Type 1	7 1/2	15	15	30	–	20	TG4323
200A	NEMA Type 1	15	25	15	50	–	–	TG4324
400A	NEMA Type 1	–	50	–	100	–	–	TG3325
600A	NEMA Type 1	–	75	–	100	–	–	TG3326
30A	NEMA Type 3R	1 1/2	3	3	7 1/2	–	5	TG4321R
60A	NEMA Type 3R	3	7 1/2	10	15	3	10	TG4322R
100A	NEMA Type 3R	7 1/2	15	15	30	–	20	TG4323R
200A	NEMA Type 3R	15	25	15	50	–	–	TG4324R
400A	NEMA Type 3R	–	50	–	100	–	–	TG3325R
600A	NEMA Type 3R	–	75	–	100	–	–	TG3326R

Fusible, Four-wire SN, 208/120 and 240 Volts AC

Ampere Rating	Enclosure Type	HP, 240 Vac, NEC Std, 1-ph	HP, 240 Vac, NEC Std, 3-ph	HP, 240 Vac, Time Delay, 1-ph	HP, 240 Vac, Time Delay, 3-ph	HP, 125 Vdc	HP, 250 Vdc	Product Number
30A	NEMA Type 1	1 1/2	3	3	7 1/2	–	5	TG4321 ¹
60A	NEMA Type 1	3	7 1/2	10	15	3	10	TG4322
100A	NEMA Type 1	7 1/2	15	15	30	–	20	TG4323
200A	NEMA Type 1	15	25	15	50	–	–	TG4324
400A	NEMA Type 1	–	50	–	100	–	–	TG4325
600A	NEMA Type 1	–	75	–	100	–	–	TG4326
30A	NEMA Type 3R	1 1/2	3	3	7 1/2	–	5	TG4321R
60A	NEMA Type 3R	3	7 1/2	10	15	3	10	TG4322R
100A	NEMA Type 3R	7 1/2	15	15	30	–	20	TG4323R
200A	NEMA Type 3R	15	25	15	50	–	–	TG4324R
400A	NEMA Type 3R	–	50	–	100	–	–	TG3325R ²
600A	NEMA Type 3R	–	75	–	100	–	–	TN165
								TG3326R ²
								TN166

No Fuse, Two-pole⁴, 240 Volts AC; 250 Volts DC (30-100 amps only); Three-pole, 240 Volts AC or Two-pole with Switching Neutral

Ampere Rating	Enclosure Type	HP, 240 Vac, NEC Std, 1-ph	HP, 240 Vac, NEC Std, 3-ph	HP, 240 Vac, Time Delay, 1-ph	HP, 240 Vac, Time Delay, 3-ph	HP, 125 Vdc	HP, 250 Vdc	Product Number
30A	NEMA Type 1	3	7 1/2	3	7 1/2	–	5	TGN3321 ¹
60A	NEMA Type 1	10	15	10	15	3	10	TGN3322 ³
100A	NEMA Type 1	15	30	15	30	–	20	TGN3323 ³
200A	NEMA Type 1	15	50	15	50	–	–	TGN3324
400A	NEMA Type 1	–	100	–	100	–	–	TGN3325
600A	NEMA Type 1	–	100	–	100	–	–	TGN3326
30A	NEMA Type 3R	3	7 1/2	3	7 1/2	–	5	TGN3321R
60A	NEMA Type 3R	10	15	10	15	3	10	TGN3322R ³
100A	NEMA Type 3R	15	30	15	30	–	20	TGN3323R ³
200A	NEMA Type 3R	15	50	15	50	–	–	TGN3324R

For Type 1 Enclosure: 200-600 amp devices available factory reversed for bottom feed. Add "B" suffix to product number (e.g., TG3224B). UL Listed.

For Type 3R Enclosure: 30-200 amp devices have removable closing cap. Order hubs for these devices separately on page 4-29. Larger amp devices require field cut openings and **customer-supplied** hub.

NEMA Type 3R No Fuse versions, 400-600 ampere rating, available in heavy duty, type TH models.

¹Packaged five per carton.

²For 4 wire applications order neutral kit separately. See page 4-24.

³Not suitable for use as service equipment. Solid neutral not available.

⁴Use three-pole switch for two-pole application.

