



PART NUMBER	TUBE OD	B UN/UNF-2A	A NPTF	L	C	D	TAP DRILL	Working Pressure
28957	1/4	7/16-20	1/8-27	1.19	0.56	0.17	0.36	3250 psi
28958	1/4	7/16-20	1/4-18	1.40	0.75	0.17	0.36	3250 psi
28959	3/8	9/16-18	1/4-18	1.40	0.75	0.30	0.48	32580 psi
28960	3/8	9/16-18	3/8-18	1.40	0.88	0.30	0.48	3250 psi
28961	1/2	3/4-16	3/8-18	1.56	0.88	0.39	0.65	3250 psi
28962	1/2	3/4-16	1/2-14	1.66	1.13	0.39	0.65	3250 psi
28963	5/8	7/8-14	1/2-14	1.87	1.13	0.48	0.77	3250 psi
28964	3/4	1-1/16-12	3/4-14	2.06	1.38	0.61	0.94	2600 psi

ASTM: B-16

TEMP RANGE: -65 ° - 250 ° F

"This drawing contains proprietary and confidential information of Midland Metal Mfg., Co. and shall not be reproduced, copied, loaned, or submitted to outside parties for examination without our consent"

NO.	PCA	Date	Revision
4			
3			
2			
1			A

TOLERANCES ARE:
DECIMALS,
.X ± 0.03
.XX ± 0.01
.XXX ± 0.005

ANGLES: ± 1 °
FRACTIONS ± 1/8

Date:	10/21/03	UNIT:	INCH
Drawn:	Rita Sue	Scale:	
Checked:		PROJECT	
Approved:			

MIDLAND METAL MFG. CO.
KANSAS CITY, MO

Material:	CA360 BRASS
Part Title:	MJIC * FNPT STRAIGHT ADAPTER

DWG. NO.	
----------	--