



PART NUMBER	TUBE OD	B UN/UNF-2A	A NPTF	L	C	D	TAP DRILL	Working Pressure
28957	1/4	7/16-20	1/8-27	1.19	0.56	0.17	0.36	3250 psi
28958	1/4	7/16-20	1/4-18	1.40	0.75	0.17	0.36	3250 psi
28959	3/8	9/16-18	1/4-18	1.40	0.75	0.30	0.48	32580 psi
28960	3/8	9/16-18	3/8-18	1.40	0.88	0.30	0.48	3250 psi
28961	1/2	3/4-16	3/8-18	1.56	0.88	0.39	0.65	3250 psi
28962	1/2	3/4-16	1/2-14	1.66	1.13	0.39	0.65	3250 psi
28963	5/8	7/8-14	1/2-14	1.87	1.13	0.48	0.77	3250 psi
28964	3/4	1-1/16-12	3/4-14	2.06	1.38	0.61	0.94	2600 psi

ASTM: B-16

TEMP RANGE: -65 ° - 250 ° F

"This drawing contains proprietary and confidential information of Midland Metal Mfg., Co. and shall not be reproduced, copied, loaned, or submitted to outside parties for examination without our consent"

NO.	PCA	Date	Revision
4			
3			
2			
1			A

  

TOLERANCES ARE: DECIMALS: .X ± 0.03 .XX ± 0.01 .XXX ± 0.005 ANGLES: ± 1° FRACTIONS ± 1/8		Date: 10/21/03	UNIT: INCH	Material: CA360 BRASS
Checked: _____	Drawn: Rita Sue	Scale: _____	PROJECT	Part Title: MJIC * FNPT STRAIGHT ADAPTER
Approved: _____				

**MIDLAND METAL MFG. CO.**  
**KANSAS CITY, MO**