

**PUSH CONNECT**

VALVES

**LEAD FREE, FULL PORT BRASS BALL VALVES PUSH-FITTING END****FEATURES**

- Dezincification Resistant (DZR) Lead Free Brass Material
- Push-Fitting conform ASSE 1061
- Forged Brass Body
- Blow Out Proof Stem Design
- Packing Nut & Packing On The Stem Seal
- Stainless Steel Ball
- Handle With Vinyl Grip

**PERFORMANCE RATING**

- 200 psi (CWP) 150 psi (WSP) Service
- Temperature Range : -20° F to 300° F

**PUSH CONNECT VALVES**

PART NO.	SIZE	DN	L	L1	L2	H	CV	WT(LBS.)	LIST
943750LF	1/2"	0.524	3.15	0.91	3.46	1.73	14.56	0.44	
943751LF	3/4"	0.748	3.55	1.10	3.46	1.89	29.76	0.55	
943752LF	1"	0.984	4.14	1.32	4.29	2.14	51.55	0.92	

PART NAME	MATERIAL
Body	Lead Free Brass
Seat	PTFE
Ball	Stainless Steel
Packing Nut	Brass
Stem	Brass
Lock Nut	Ferrum /Zinc Plated
Lock Washer	Ferrum /Zinc Plated
Packing	PTFE
Handle	Ferrum /Chrome Plated
Cap	Lead Free Brass
O-RING	EPDM
Seat Ring	POM
Gripper Ring	Stainless Steel
Push Ring	POM
Lock Ring	POM
Liner	PSF

