# HIGH PRESSURE SPRAYERS



## **STRAIGHT THROUGH QDS**



**NOZZLES** 



### **FITTINGS AND SWIVELS**



## **SPRAY GUNS AND WANDS**





# **NOZZLES**



# OFFERED EXCLUSIVELY THROUGH MIDLAND



### **QUICK DISCONNECT NOZZLE**

0-degree red tip nozzle, 15-degree yellow tip nozzle, 25-degree green tip nozzle, 40-degree white tip nozzle, and 65-degree black tip detergent nozzle. All nozzles are 4000 PSI and stainless steel, except for detergent nozzle, which is 600 PSI and brass. All Nozzles are rated for temperatures up to 300°F. Nozzles attach with 1/4" quick disconnect plug.











PART #	DEGREE OF SPRAY	GPM @ 4000PSI	
DX250030	0	3.0	
DX251530	15	3.0	
DX252530	25	3.0	
DX254030	40	3.0	
DX250040	0	4.0	
DX251540	15	4.0	
DX252540	25	4.0	
DX254040	40	4.0	
DX250050	0	5.0	
DX251550	15	5.0	
DX252550	25	5.0	
DX254050	40	5.0	
DX250060	0	6.0	
DX251560	15	6.0	
DX252560	25	6.0	
DX254060	40	6.0	
DX256500	65		

### **MEG NOZZLE**

Available in 0-degree nozzle, 15-degree nozzle, 25-degree nozzle, or 40-degree nozzle. Nozzle sizes 3.0, 4.0, 5.0, 6.0 or 7.0. All nozzles are 7250 PSI 300°F, stainless steel and 1/4" male pipe thread.



PART #	DEGREE OF SPRAY	GPM @ 4000PSI	
DX140030MG	0	3.0	
DX141530MG	15	3.0	
DX142530MG	25	3.0	
DX144030MG	40	3.0	
DX140040MG	0	4.0	
DX141540MG	15	4.0	
DX142540MG	25	4.0	
DX144040MG	40	4.0	
DX140050MG	0	5.0	
DX141550MG	15	5.0	
DX142550MG	25	5.0	
DX144050MG	40	5.0	
DX140060MG	0	6.0	
DX141560MG	15	6.0	
DX142560MG	25	6.0	
DX144060MG	40	6.0	
DX140070MG	0	7.0	
DX141570MG	15	7.0	
DX142570MG	25	7.0	
DX144070MG	40	7.0	

## **QUICK DISCONNECT NOZZLE 5-PIECE KIT**

PART #	GPM @ 4000PSI	
DX259520	2.0	
DX259530	3.0	
DX259540	4.0	
DX259550	5.0	
DX259560	6.0	
DX259570	7.0	



WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

# **SWIVELS**



# OFFERED EXCLUSIVELY THROUGH WIDLAND



### RUBBER-TIP TURBO NOZZLE

Rubber tip, rotating turbo nozzle, 1/4" NPT with steel male quick disconnect plug adaptor, rated for temperatures up to 300°F.



PART #	PSI	GPM @ 4000PSI	
DX722530	2500	3.0	
DX722540	2500	4.0	
DX722550	2500	5.0	
DX722560	2500	6.0	
DX723230	3200	3.0	
DX723240	3200	4.0	
DX723250	3200	5.0	
DX723260	3200	6.0	
DX724030	4000	3.0	
DX724040	4000	4.0	
DX724050	4000	5.0	
DX724060	4000	6.0	
DX725030	5000	3.0	
DX725040	5000	4.0	
DX725050	5000	5.0	
DX725060	5000	6.0	

### STAINLESS STEEL LIVE SWIVEL

MxF straight through live swivel, NBR or Viton seal, 416 SS, 10.6 gpm, 180F max, 3500 PSI



PART #	SEAL	SIZE	
DX60021	NBR	1/4"	
DX60022	NBR	3/8"	
DX60023	NBR	1/2"	
DX60021V	Viton	1/4"	
DX60022V	Viton	3/8"	
DX60023V	Viton	1/2"	

### THERMAL RELIEF VALVE

140F Thermal Relief Valve, Brass, 300 PSI

Attaches directly to pump



	PART #	SIZE	
ı	DX35TR25	1/4"	
ĺ	DX35TR38	3/8"	

### 90° BOOM SWIVEL

Male x Female 90° Boom swivel, Stainless Steel, 5000 PSI, 7GPM, 300°F



PART#	SIZE	
DX60092	3/8"	

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

# **SPRAYERS**



# OFFERED EXCLUSIVELY THROUGH WID

### CHROMED STEEL WAND

1/4" MNPT x 1/4" Extension Wands, 10.5 GPM, 300F



PART #	SIZE	GRIP	
DX4324	24"	No Grip	
DX4336	36"	No Grip	
DX4424	24"	Molded Grip	
DX4436	36"	Molded Grip	
DX4524VG	24"	Vented Grip	
DX4536VG	36"	Vented Grip	

### **SPRAY GUN**

Rear entry spray gun, 4000 PSI, 7 GPM, 212F max, inlet 3/8", outlet 1/4"



PART #	PRESSURE	FLOW	TEMPERATURE	
DX5090	4000	7	212	
DX5022	4000	6.6	300	
DX5005	5075	10.5	300	

### WEEPING SPRAY GUN

Rear entry spray gun, weeping, 5000 PSI, 10.5 GPM, 300F, , inlet 3/8", outlet 1/4"

Weep style spray guns allow for a continuous flow of water by way of a small hole in the bottom of the gun that produces a slight leak, or a weeping effect. This helps prevent lines freezing in cold weather or scalding water temperatures in hot weather that could damage the pumps.



PARI#	
DX5006	

### SPRAY GUN WITH EXTENSION\*

Rear entry spray gun with 12" extension, 4000psi, 7gpm, 300F max, inlet 3/8", outlet M22



### **SPRAY GUN WITH EXTENSION\***

Rrear entry spray gun with 12" extension, 5075psi, 10.5gpm, 300F max, inlet 3/8", outlet M22



PART #	
DX5197	

\*Requires a 86-005 for MEG Nozzle and a 86-005 & 86-030 for QD Nozzle

WARNING: This product can expose you to chemicals, including Chromium, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov

### **COUPLERS/PLUGS**

HIGH PRESSURE SPRAYER

# **QUICK DISCONNECTS**

- Brass couplers have brass bodies and brass valves, 8 steel locking balls, Buna-N seal, and stainless steel springs
- Stainless steel couplers have stainless steel bodies, 8 stainless steel locking balls, Buna-N seal, and stainless steel springs
- Plugs are steel with green blue zinc plating or stainless steel
- Straight through design means there is no positive shut-off after disconnect
- Fully interchangeable with Parker, Hansen, Foster and Adams
- Use with liquids, hydraulic service, compressed air, gases, water and vacuum
- Ideal for applications such as high pressure water, steam washers, and carpet cleaners
- Max. Temp. 212°F for Couplers/ 300°F for Plugs
  Max Flow: 10.5 GPM

#### STRAIGHT THROUGH STYLE

### MALE BRASS COUPLERS



PART #	BODY SIZE	THREAD SIZE	PSI	
86030	1/4	1/4	4000	
86031	3/8	3/8	4000	
86032	1/2	1/2	4000	

### FEMALE BRASS COUPLERS



PART #	BODY SIZE	THREAD SIZE	PSI	
86035	1/4	1/4	4000	
86036	3/8	3/8	4000	
86037	1/2	1/2	4000	

#### MALE STAINLESS STEEL COUPLERS



PART #	BODY SIZE	THREAD SIZE	PSI	
86030SS	1/4	1/4	6000	
86031SS	3/8	3/8	6000	

### FEMALE STAINLESS STEEL COUPLERS



PART #	BODY SIZE	THREAD SIZE	PSI	
86035SS	1/4	1/4	6000	
86036SS	3/8	3/8	6000	

#### MALE STEEL PLUGS



PART #	BODY SIZE	THREAD SIZE	PSI	
86040	1/4	1/4	4000	
86041	3/8	3/8	4000	
86042	1/2	1/2	4000	

### FEMALE STEEL PLUGS



PART #	BODY SIZE	THREAD SIZE	PSI	
86045	1/4	1/4	4000	
86046	3/8	3/8	4000	
86047	1/2	1/2	4000	

### MALE STAINLESS STEEL PLUGS



PART #	BODY SIZE	THREAD SIZE	PSI	
86040SS	1/4	1/4	6000	
86041SS	3/8	3/8	6000	

### **FEMALE STAINLESS STEEL PLUGS**



PART #	BODY SIZE	THREAD SIZE	PSI	
86045SS	1/4	1/4	6000	
86046SS	3/8	3/8	6000	

## **COUPLERS/KNOBS**

HIGH PRESSURE SPRAYER

### **MOLDED GRIP MALE BRASS COUPLER**



PART #	THREAD SIZE	THREAD SIZE	PSI	
86030RG	1/4	1/4	4000	
86031RG	3/8	3/8	4000	

### **MOLDED GRIP FEMALE BRASS COUPLER**



PART #	THREAD SIZE	PLUG	PSI	
86035RG	1/4	1/4	4000	
86036RG	3/8	3/8	4000	

### **M22 SCREW TYPE X MNPT**



PART #	THREAD SIZE	MALE	PSI	
86001	M22	1/4	4000	
86002	M22	3/8	4000	

### **M22 SCREW TYPE X FNPT**



PART #	THREAD SIZE	FEMALE SIZE	PSI	
86005	M22	1/4	4000	
86006	M22	3/8	4000	

## **INSULATED KNOB**

### **M22 INSULATED KNOB X MNPT**



PART #	THREAD SIZE	MALE SIZE	PSI	
86012	M22	1/4	4000	
86013	M22	3/8	4000	

### **M22 INSULATED KNOB X FNPT**



PART #	THREAD SIZE	FEMALE SIZE	PSI	
86017	M22	1/4	4000	
86018	M22	3/8	4000	

### M22 X M22 FNPT



PART #	THREAD SIZE	THREAD SIZE	PSI	
	SIZE	SIZE		
86022	M22	M22	4000	

### M22 INSULATED KNOB X QC PLUG



PART #	THREAD SIZE	PLUG	PSI	
86020	M22	3/8	4000	 5