

TF1 TOTAL FILTER

- Hydrocyclonic and magnetic in-line filter
- Unique action, removes all contaminants magnetic and non-magnetic
- Fits vertical and horizontal pipe work
- Dosing point for Fernox 'F' range products
- Cleaned in seconds without removal or disassembly
- Will not block or restrict flow
- All valves and fittings included



Product Specifications

- Maximum temperature 257°F
- Maximum working pressure 3 bar
- Maximum flow rate 11 gallons/min
- Magnetic characteristics - 9000 Gauss Neodymium magnet assembly
- Glass fibre reinforced Nylon plastic

Product Uses

The Fernox Total Filter TF1 (UK patent pending 0806091.5) is a revolutionary in-line filter, which combines hydrocyclonic action with specially designed magnet assemblies, to remove both magnetic and non-magnetic contaminants from system water and contain safely within the filter.

Application

The Fernox Total Filter TF1 can be connected directly onto 1" sweat pipe work using the valve fittings provided. The unit can be installed in either horizontal or vertical pipe work and has been conveniently designed to be installed flush to a wall in existing pipe work. The TF1 can be installed in any orientation including flow right to left and flow up and down, a conversion kit is supplied with the unit or available from our Sales Office by calling 1-800-289-3797. Further installation instructions are provided with the unit.

Packaging, Handling and Storage

Individually packaged with all connectors and detailed instructions included. No special storage requirements needed.