

# TRUFLEX™ - LIGHT DUTY

## WRAPPED, FRACTIONAL HORSEPOWER V-BELT

Engineered with all the qualities of a great belt, including flexibility, durability, and resistance to contaminants. It includes a thin profile, designed for small-diameter sheaves, and a lower cord positioning to improve belt performance on light-duty belt drives and in your backside idler applications.

### CONSTRUCTION + SPECIFICATIONS

- **Gates Curves** provide proper cord support and full contact with the sheave-groove for uniform loading, uniform wear, and increased belt life.
- **Flex-Bonded cords** are strongly bonded to the body of the belt resulting in equal load distribution and the absorption of bending stress without cord deterioration.
- **Flex-Weave™** oil and heat resistant cover protects the belt core from the toughest environments.

### FEATURES + BENEFITS

- Perfect for auxiliary automotive applications like electric windows, windshield wipers, and central locking systems, drive pumps, power tools, and domestic appliance applications, FHP motors and light-duty applications.
- Meets ARPM/RMA IP-3-2 oil and heat resistant standards.
- Meets ARPM/RMA IP-3-3 static conductivity requirements.
- REACH and RoHS 2 compliant.
- Operating temperature range: -30°C/-22°F to +60°C/140°F.

### BELT IDENTIFICATION

Singles: **3L280**

**3L** - Cross Section

**280** - Outside Circumference (in), plus added zero to designate part number

#### Available Stock Sizes

**2L** 10-46 (in)

**3L** 11-74 (in)

**4L** 15-100 (in)

**5L** 23-100 (in)



Belt Identification Chart

1/4" 1/8"	3/8" 7/32"	1/2" 5/16"	21/32" 3/8"
<b>2L (0)</b>	<b>3L (1)</b>	<b>4L (2)</b>	<b>5L (3)</b>